LV-OP-1-4

Performance of artificial intelligence in predicting survival following deceased donor liver transplantation: Retrospective study using multi-center data from the Korean Organ Transplant Registry (KOTRY)

Young-Dong YU^{*1}, Kwang-Sig LEE², Hye-Sung JO¹, Dong-Sik KIM¹

¹Department of Surgery, Korea University Anam Hospital, Seoul, Korea

²AI Center, Korea University College of Medicine, Seoul, Korea

Introduction: Although the Model for End-stage Liver Disease (MELD) score is commonly used to prioritize patients awaiting liver transplantation, previous studies have indicated that MELD score may fail to predict well for the postoperative patients. Similarly, other scores (D-MELD score, balance of risk score) that have been developed to predict transplant outcome have not gained widespread use. These scores are typically derived from linear statistical models. The aim of this study was to compare the performance traditional statistical models with machine learning approaches in predicting survival following liver transplantation using multi-center data.

Methods: Data came from 785 deceased donor liver transplant recipients enrolled in the Korean Organ Transplant Registry (KOTRY, 2014–2019). Five machine learning methods and 4 traditional statistical models were compared for the prediction of survival.

Results: Of the machine learning methods, random forest (RF) yielded the highest area under the receiver operating characteristic curve (AUC-ROC) values (1 month = 0.89, 3 month = 0.92, 12 month = 0.87) for predicting survival. The AUC-ROC values of Cox regression analysis was 0.76, 0.85 and 0.80 for 1 month, 3 month and 12 month posttransplant survival, respectively. However, the AUC-ROC values of the MELD, D-MELD, and BAR score were all below 0.70.

Conclusions: Machine learning algorithms such as random forest was superior than the conventional cox regression model and previously reported survival scores in predicting 1 month, 3 month, 12 month survival following liver transplantation. Therefore, artificial intelligence may have significant potential in providing assistance with clinical decision making during liver transplantation including matching donors and recipients.

Corresponding Author: Young-Dong YU (hust1351@naver.com)

Presenter: Young-Dong YU (hust1351@naver.com)

Copyright © The Korean Association of Hepato-Biliary-Pancreatic Surgery

This is an Open Access article distributed under the terms of the Creative Commons Attribution Non-Commercial License (<http://creativecommons.org/licenses/by-nc/4.0>) which permits unrestricted non-commercial use, distribution, and reproduction in any medium, provided the original work is properly cited.